

Q, kW	Temperaturni režim: 140-80/70-90					Temperaturni režim: 120-75/70-90				
	Tip izmenjivača toplote	V_1 / V_2 l/s		$\Delta p_1 / \Delta p_2$ kPa		Tip izmenjivača toplote	V_1 / V_2 l/s		$\Delta p_1 / \Delta p_2$ kPa	
20	LSL0-10	0.083	0.245	3	15	LSL0-20	0.11	0.24	1	4
30	LSL0-12	0.125	0.367	4	23	LSL0-28	0.16	0.37	1	5
40	LSL0-16	0.166	0.489	3	23	LSL0-34	0.22	0.49	1	6
50	LSL0-20	0.208	0.612	3	23	LSL0-42	0.27	0.61	1	6
60	LSL0-24	0.249	0.734	3	23	LSL0-50	0.33	0.73	1	6
70	LSL0-28	0.291	0.856	3	24	LSL0-58	0.38	0.86	1	6
80	LSL0-32	0.332	0.978	3	24	LSL0-66	0.44	0.98	1	6
90	LSL0-36	0.374	1.101	3	24	LSL1-12	0.49	1.1	3	10
100	LSL0-40	0.415	1.223	3	24	LSL1-14	0.55	1.22	3	9
110	LSL0-44	0.457	1.345	3	24	LSL1-14	0.6	1.35	3	10
120	LSL0-48	0.498	1.468	3	24	LSL1-16	0.66	1.47	3	10
130	LSL0-52	0.54	1.59	3	24	LSL1-16	0.71	1.59	3	11
140	LSL0-54	0.582	1.712	3	25	LSL1-18	0.77	1.71	3	10
150	LSL1-58	0.623	1.835	3	25	LSL1-18	0.82	1.83	3	12
200	LSL1-16	0.831	2.446	4	24	LSL1-24	1.1	2.45	3	12
250	LSL1-20	1.038	3.058	4	24	LSL1-28	1.37	3.06	4	13
300	LSL1-24	1.246	3.669	4	24	LSL1-34	1.65	3.67	3	13
350	LSL1-28	1.454	4.281	4	24	LSL1-38	1.92	4.28	4	14
400	LSL1-32	1.661	4.892	4	24	LSL1-44	2.19	4.89	4	14
450	LSL1-36	1.869	5.504	4	24	LSL1-48	2.47	5.5	4	14
500	LSL1-40	2.077	6.115	4	24	LSL1-54	2.74	6.12	4	14
600	LSL1-46	2.492	7.338	4	25	LSL1-64	3.29	7.34	4	14
700	LSL1-54	2.908	8.561	4	25	LSL1-74	3.84	8.56	4	15
800	LSL1-62	3.323	9.784	4	25	LSL1-84	4.39	9.78	4	15
900	LSL1-70	3.738	11.01	4	25	LSL1-94	4.94	11.01	4	15
1000	LSL1-78	4.154	12.23	4	25	LSL1-104	5.49	12.23	4	15
1100	LSL1-86	4.569	13.45	4	25	LSL1-114	6.04	13.45	4	16
1200	LSL1-96	4.984	14.68	4	24	LSL1-124	6.58	14.68	4	16
1300	LSL1-104	5.4	15.9	4	24	LSL2-66	7.13	15.9	6	25
1350	LSL2-68	5.607	16.51	3	25	LSL2-70	7.41	16.51	5	24
1400	LSL2-72	5.815	17.12	3	24	LSL2-72	7.68	17.12	5	24
1500	LSL2-76	6.231	18.35	3	25	LSL2-76	8.23	18.35	6	25
1600	LSL2-82	6.646	19.57	3	25	LSL2-82	8.78	19.57	6	25
1700	LSL2-86	7.061	20.79	3	25	LSL2-86	9.33	20.79	6	25
1800	LSL2-92	7.477	22.02	3	25	LSL2-92	9.88	22.01	5	25
1900	LSL2-96	7.892	23.24	3	25	LSL2-96	10.43	23.24	6	25
2000	LSL2-102	8.307	24.46	3	25	LSL2-102	10.97	24.46	5	25
2100	LSL2-106	8.723	25.68	3	25	LSL2-106	11.52	25.68	6	25
2200	LSL2-112	9.138	26.91	3	25	LSL2-112	12.07	26.91	5	25
2300	LSL2-116	9.553	28.13	3	25	LSL2-118	12.62	28.13	5	25
2400	LSL2-124	9.969	29.35	3	24	LSL2-124	13.17	29.35	5	24
2500	LSL2-126	10.38	30.58	3	25	LSL2-128	13.72	30.58	5	25
2600	LSL2-134	10.8	31.8	3	24	LSL2-134	14.27	31.8	5	24
2700	LSL2-138	11.22	33.02	3	25	LSL2-138	14.82	33.02	5	25
2800	LSL2-144	11.63	34.25	3	25	LSL2-144	15.36	34.25	5	25
2900	LSL2-148	12.05	35.47	3	25	LSL2-148	15.91	35.47	5	25
3000	LSL2-154	12.46	36.69	3	25	LSL2-154	16.46	36.69	5	25
3100	LSL2-160	12.88	37.91	3	24	LSL2-160	17.01	37.91	5	24
3200	LSL2-162	13.29	39.14	3	25	LSL2-164	17.56	39.14	5	25